

TAIWAN LIH TAY

The first manufacturer of instant noodle production equipment in Taiwan.

And The Best



TAIWAN LIH TAY MACHINERY CO., LTD.

NO.66, SEC.1, SZU-HAI RD, PEI-TOU, CHANG-HUA, TAIWAN, R.O.C.
TEL:+886-4-8887781 FAX:+886-4-8887784 SALES:+886-4-8886160
<http://www.lihtay.com.tw> E-mail:business@lihtay.com.tw



AUTOMATIC BAG INSTANT NOODLE PRODUCTION LINE

A combination of 35-year-more experience and technology know-how



TOTAL TECHNOLOGY SUPPORT

- PROJECT PLANNING
- DESIGN
- EQUIPMENT SUPPLY
- INSTALLATION ASSISTANCE
- OPERATION TRAINING

SINCE 1968



AUTOMATIC BAG INSTANT NOODLE PRODUCTION LINE

LTI-800 Brief Introduction

1. Production Capacity: 230,000 Bags / 8 Hours
2. Noodle Weight: 60 ~ 80g
3. Production Parameters
 - Plant Space Required: 96M (L) X 12M (W) X 7M (H)
(Office and warehouse for raw materials & finished products are excluded)
 - Power Consumption: 152Kw (Main Production Line)
 - Steam Boiler: 5,000Kg / Hour
 - Working Pressure: 10Kg / Cm²
 - Water (Soft Water) Consumption: 7,000Kg / Hour
 - Frying Oil Consumption: 3,700Kg / 8 Hour
 - Operator Required: (a) About 4 persons before packing process
(b) About 11 persons for packing operation

LTI-600 Brief Introduction

1. Production Capacity: 150,000 Bags / 8 Hours
2. Noodle Weight: 60 ~ 80g
3. Production Parameters
 - Plant Space Required: 96M (L) X 12M (W) X 7M (H)
(Office and warehouse for raw materials & finished products are excluded)
 - Power Consumption: 136Kw (Main Production Line)
 - Steam Boiler: 4,000Kg / Hour
 - Working Pressure: 10Kg / Cm²
 - Water (Soft Water) Consumption: 6,000Kg / Hour
 - Frying Oil Consumption: 2,500Kg / 8 Hour
 - Operator Required: (a) About 4 persons before packing process
(b) About 11 persons for packing operation

LTI-500 Brief Introduction

1. Production Capacity: 100,000 Bags / 8 Hours
2. Noodle Weight: 60 ~ 80g
3. Production Parameters
 - Plant Space Required: 96M (L) X 12M (W) X 7M (H)
(Office and warehouse for raw materials & finished products are excluded)
 - Power Consumption: 120Kw (Main Production Line)
 - Steam Boiler: 3,000Kg / Hour
 - Working Pressure: 10Kg / Cm²
 - Water (Soft Water) Consumption: 5,000Kg / Hour
 - Frying Oil Consumption: 1,600Kg / 8 Hour
 - Operator Required: (a) About 4 persons before packing process
(b) About 11 persons for packing operation



SODA WATER STORAGE TANK



FLOUR SIEVING MACHINE



WATER TANK WITH LEVEL CONTROLLER & MIXER



RATIONING CUTTING OUTLET & SEASONING CONVEYOR



OIL STORAGE BARREL & HEAT EXCHANGER



COOLING MACHINE



NOODLE CONVEYOR



PACKING MACHINE



MATERIAL FEEDING & COMPOUNDING MACHINE



ROLLING STRETCHING MACHINE



STEAMING MACHINE



FRYING MACHINE



DISTRIBUTING MACHINE



DISTRIBUTING CONVEYOR



CARTON SEALING MACHINE



PLC ELECTRICAL CONTROL PANEL