

The Advanced Manufacturing Equipment

Lih Tay's machines are manufactured in our modern facility. At the heart of our production capability lies on the wide range of advanced manufacturing equipment, such as laser cutting machines for steel plates, CNC machine centers, highly skilled technicians. All these provide a solid foundation for the high performance machines.

EXCELLENT DESIGN LAYS A SOLID FOUNDATION FOR HIGH AVAILABILITY

Beginning with proven, reliable design, Lih Tay's engineer experts in machinery, electrical control, noodle material properties and manufacturing processes visualize and configure equipment that efficiently and economically meet your rigorous demands of each instant noodle production project.



CNC-Lathe



CNC-Miller




Machine Center



Laser Cutting



Hydraulic Press Brake



Laser Cutting



Machine Arm



Factory View I



Factory View II

TAIWAN LIH TAY

The first manufacturer of instant noodle production equipment in Taiwan.

And The Best



TAIWAN LIH TAY MACHINERY CO., LTD.

NO.66, SEC.1, SZU-HAI RD, PEI-TOU, CHANG-HUA, TAIWAN, R.O.C.
TEL:+886-4-887781 FAX:+886-4-887784 SALES:+886-4-8886160
<http://www.lihtay.com.tw> E-mail:business@lihtay.com.tw



AUTOMATIC BOWL/CUP INSTANT NOODLE PRODUCTION EQUIPMENT

A combination of 35-year-more experience and technology know-how



TOTAL TECHNOLOGY SUPPORT

- PROJECT PLANNING
- DESIGN
- EQUIPMENT SUPPLY
- INSTALLATION ASSISTANCE
- OPERATION TRAINING

SINCE 1968



AUTOMATIC BOWL/CUP INSTANT NOODLE PRODUCTION LINE

- LTC-600 (A) Brief Introduction**
1. Production Capacity: 100,000 Bowl / Cup / 8 Hours
 2. Noodle Weight: 60~70g
 3. Production Parameters
 - Plant Space Required: 19.2M (L) X 12.1M (W) X 7M (H)
 - Office and warehouse for raw materials & finished products are excluded
 - Power Consumption: 105kw (Main Production Line)
 - Steam Boiler: 1,000kg / Hour
 - Working Pressure: 10kg / Cm²
 - Water (Soft Water) Consumption: 5,000kg / Hour
 - Frying Oil Consumption: 1,000kg / 8Hour
 - Operator Required: (a) About 5 persons before packing machine (b) About 3 persons after packing machine

- LTC-600 (B) Brief Introduction**
1. Production Capacity: 100,000 Cup / 8 Hours
 2. Noodle Weight: 50~70g
 3. Production Parameters
 - Plant Space Required: 13.2M (L) X 12.1M (W) X 7M (H)
 - Office and warehouse for raw materials & finished products are excluded
 - Power Consumption: 230kw (Main Production Line)
 - Steam Boiler: 3,000kg / Hour
 - Working Pressure: 10kg / Cm²
 - Water (Soft Water) Consumption: 5,000kg / Hour
 - Frying Oil Consumption: 1,000kg / 8Hour
 - Operator Required: (a) About 5 persons before packing machine (b) About 10 persons after packing machine

LTC-600(A)

LTC-600(B)

